

Standalone Panel Antenna 4.94-4.99GHz 23dBi



- ◆ Innovative / cost effective / patented circuit design
- ◆ UV stabilized plastic / rugged design for outdoor use
- ◆ Low Profile
- ◆ Articulating wall/pole bracket (BRA-A-1699-02) included
- ◆ Custom radome design service available to OEMs
- ◆ Custom groundplane available for OEM integration

ARC-PA4923B01

Electrical Specifications	
Frequency Range	4.94-4.99GHz
Gain	23dBi
3dB Beamwidth Vertical/Horizontal	8.5deg/10deg
Polarization	Single linear, horizontal or vertical
VSWR	≤1.7:1
Power Rating	30 watts
Impedance	50 ohms
Lighting Protection	DC ground
Connector Type	N Jack

Ordering Information	
Part #	Description
ARC-PA4923B01	4.94-4.99GHz 23dBi Panel Antenna, N Jack

Shipping Information	
Sizes and Weights	Description
22in x 19in x 19in (55.9cm x 48.3cm x 48.3cm) 41lb, (18.6kg)	Packaging includes 10 units, including 10 mounting bracket kits in a single over pack box


Standalone Panel Antenna

4.94-4.99GHz 23dBi



Mechanical and Environmental Specifications	
Length x Width x Depth	15.4in x 15.4in x 1.7in (39.1cm x 39.1cm x 4.3cm)
Weight	2.9 lb (1.32 kg)
Backplane	Aluminum
Radome	UV stabilized ABS plastic
Wind Survivability	125mph (201kph)
Wind Load	1.23ft ² (0.12m ²)
Operating Temperature Range	-49°F to +149°F (-45°C to +65°C)
Pole Mount Diameter Range	0.75in to 2.0in (1.9cm to 5.1cm)

RF Patterns
Vertical Cut, typ.



RF Patterns
Horizontal Cut, typ.

